

# Product Information Sheet



## Top Shield™ / Mop On Style Wax

### PRODUCT NAME

**Concrete Camouflage®  
Top Shield™ / Floor Wax**

### PRODUCT DESCRIPTION

A water-based mop on style floor wax, formulated with acrylic resins, designed for long life, tough as nails finish, and quick drying time. TOP SHIELD™ is resistant to ultraviolet rays, and wet and dry abrasion. The resins in our wax, specially formulated, has a very high resistance to traffic, lasting for months in high traffic areas. Highly recommended for interior use.

### CAN BE USED FOR

- A. Sealed or very smooth concrete.
- B. Any Sealed Surface.

### BENEFITS

TOP SHIELD™ is industrial grade. Designed for professional use.

TOP SHIELD™ provides a higher resistance to traffic, longer life, and quicker drying time than cheaper waxes or floor finishes.

TOP SHIELD™ adds luster and shine while being extremely low maintenance. You never need a buffing machine, though one can be used if desired.

Contains UV Inhibitors.

TOP SHIELD™ is extremely scuff resistant, less slippery than sealed concrete alone, and very user friendly

### APPLICATION

**Preparation:** Concrete must be at least 12 days old, clean and completely dry. Free from old paints, oil, grease, waxes, floor finishes, acid stain residues,

excess release agents, and any other contaminants which might prevent adhesion or negatively affect the bond. We recommend that the surface be sealed and cured prior to wax application.

**Application:** Do Not pour TOP SHIELD™ directly onto surface. Use a roller pan. Apply thin even coats using a lambs wool Applicator, synthetic fiber wax Applicator, or sponge mop. Do not flood coat ( apply too thick). Material is designed to be applied as thin of a coat as you can. Apply in one direction to an even, consistent, uniform finish. Work out puddles and pinholes. Let dry between coats. A second coat should be applied after the first coat has completely dried, usually after a minimum of 1 hour, when applying for the first time. Although buffing is not required, it can be machine buffed after 1-4 hours for increased sheen.

**Wax Removal:** Can be recoated up to 100 times without the need for stripping. To strip wax, simply use ammonia and water.

**Cleanup:** Clean all tools immediately with warm water.

**Coverage:** 1000-2000 square feet per gallon ( 1-3 wet mils )

**Usual Average Coverage:**

1 Gallon = 1600 Sq.Ft.

32 Ounce = 400 Sq.Ft.

8 Ounce = 100 Sq.Ft.

### MAINTENANCE

Surfaces that are waxed with TOP SHIELD™, are easy to maintain

and can be cleaned by sweeping and washing with a mop and water. Use a mild detergent as needed. Add a fresh coat of wax as needed.

### SAFETY PRECAUTIONS

**Warning:** Skin and Eye irritant. Wear rubber gloves and eye protection. If splashed in **eye**, flush with cool running water for at least 15 minutes. Raising the eyelid to ensure complete cleansing of the eye. Get medical attention. For **skin** contact, wash with soap and water. For **inhalation**, remove to fresh air. Use with adequate ventilation. If **swallowed**, drink two glasses of water and induce vomiting. Get medical attention. Keep closed when not in use. Keep away from sparks or flame. **KEEP AWAY FROM CHILDREN.**

### DRYING TIME

Depends on weather conditions such as temperature and humidity. Usually 1 to 2 hours between coats. Allow to dry overnight before foot traffic.

### PACKAGING

1 Gallon, 32 Ounce, and 8 Ounce.

### AVAILABILITY

Available through hardware stores, builder and contractor stores, and nurseries, or contact manufacturer

### IMPORTANT NOTICE

Manufacturer's and Seller's Condition of Sales:

The material is guaranteed to be of standard quality and to conform to

Continued>

# Information Sheet

Page 2 of 2

## — Top Shield™ / Mop On Style Wax —

our published specifications. Since we do not control the use and application of this product, nor the areas to which it is applied, we disclaim any and all responsibility or warranties, expressed or implied, in connection with its handling, its use and storage, or the results obtained.

Likewise, we disclaim any and all responsibility or warranties, expressed or implied, in connection with any injury or damage of any nature, whatsoever, resulting from its uses. Also excluded is any warranty of merchantability.

### **LIMITED WARRANTY**

Camouflaged Concrete Corp. warrants its products to be of good quality and will replace any product proven defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement, Camouflaged Concrete Corp. makes no warranty or guarantee expressed or implied, including warranties of fitness for a particular purpose or merchantability, respecting its products, and Camouflaged Concrete Corp. shall have no other liability with respect thereto, including without limitation, liability for incidental or consequential damages. Any claim regarding product defect must be received in writing within (180) days from the date of shipment. No claim will be considered without such written notice or after the specified time interval the user shall determine the suitability of the products for the intended use and assumes all risk and liability in connection therewith.

**Also available:** Printed or in PDF.

Architect Specs.  
Color Charts.  
Supplies Checklist.  
& More.

**ConcreteCamouflage.com**

P.O. Box 51  
Farmersville, Tx 75442  
**800 / 650 - 1157**

*Camouflage Your Concrete!*™